

# NamaGrit™


## Granulated Abrasives

NamaGrit is an efficient blasting abrasive manufactured from selected copper slag raw materials and delivered clean, dry and perfectly graded for optimum performance.

### PHYSICAL PROPERTIES

Properties	Test Method	SSPC AB1 Requirements	NamaGrit™ (Typical)	Check
Specific Gravity	ASTM C-128	>2.5	3.2	✓
Hardness	Mohs Scale	>6	>7	✓
Soluble salts (Conductivity)	ASTM D4940	<100ms/m	18 - 35µS/cm	✓
Moisture Content	ASTM C-566	<0.5%	<0.1%	✓
Oil Content	Observe surface of water extract	none	none	✓
Free Silica	X-Ray Diffraction	<1%	< 0.5%	✓

### STANDARD GRADES AVAILABLE

Grade	mm size range	Surface Profiles achieved	Applications
NG90 	0.25 – 1.8mm	75 - 120µ	<b>General purpose</b> – Best all round performance under typical operating conditions (6 – 7 Bar nozzle pressure)

### PACKAGING OPTIONS

50kg bags packed 24 per 1.2 ton bulk bag	1.5 ton bulk bags	Plastic liners in bulk bags optional
--	-------------------	--------------------------------------